


Sectional Terminal Blocks

7/16" Sectional Terminal Block

600 Volts AC/DC, 40 Amp
27 Circuits per Foot

Specifications:

- UL Recognized File No. XCFR2.E62806, XCFR8.E62806
- CSA Certified File No. LR19766
- 
- RoHS Compliant



6G44 SP DIN

6G44 SP DIN - Sems Pressure Connector, DIN Mounted






Materials:

- Base - Gray Thermoplastic, 125°C (UL RTI)
- Connector - Brass, Tin Plated
- Screw - #6 with pad, Steel, Nickel Plated

Wire Ranges:

- CU Only, Str/Sol
 - Base Wire:
 - (1) #12-#22 AWG
 - (1-2) #22-12 AWG
 - Classes B, C, G, H, I, K
- Prepared Wire (Lug or Spade):
- (1) #10-#16 AWG
 - (1-2) #10-16 AWG
- Wire Termination Torque 10 lb-in

Sectional Terminal Block Accessories

| Catalog # | Description | | Std Pk |
|------------|---------------------------------------|---|--------|
| 6G44 E DIN | End Sections |  | 25 |
| MS 44 | 7/16 marker strip (4' long, white) |  | 6 |
| 601 RJS XX | Jumper (various lengths) |  | N/A |
| MSK35 | End Bracket for DIN Rail |  | 25 |
| MN35-2 | DIN Rail 35 x 7.5 mm 2m long, slotted |  | N/A |

For electronic drawings or 2D/3D CAD data, send request to drawings@marathonsp.com

